

Q8 Auto 14

Automatic transmission fluid

Description

Q8 Auto 14 is an advanced transmission fluid for various applications, mainly heavy duty. The product is recommended for automatic transmissions meeting Dexron IID performance and the related power steering systems.

Applications

Q8 Auto 14 is recommended for automatic transmissions meeting Dexron IID performance and the related power steering systems. It is suitable for automatic transmissions in most passenger cars, buses, construction and military equipment and in selected manual transmissions, but also as power steering and hydraulic fluid. It meets ZF, Voith, Allison, Volvo, Ford, MAN and MB specifications.

Benefits

- Advanced protection against wear and extends component life.
- High protection against rust and corrosion.
- Cold starting improvement.

Specifications, recommendations and approvals

Allison	C-4	MB	236.7
Ford	M2C 138-CJ	Voith	H55.6335.xx
Ford	M2C 166-H	Volvo	97325
Ford	M2C 185-A	Volvo	97335
Ford	M2C 186-A	Volvo	97340
GM	6137M	ZF	TE-ML 02F
GM	Dexron II D	ZF	TE-ML 03D
Komatsu Dresser	B22-0004	ZF	TE-ML 04D
MAN	339 Type L2	ZF	TE-ML 09
MAN	339 Type V1	ZF	TE-ML 11A
MAN	339 Type Z1	ZF	TE-ML 14A
MB	236.1	ZF	TE-ML 17C
MB	236.5		

Color code blue = officially approved

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,87
Kinematic Viscosity, 40 °C	D 445	mm ² /s	35.9
Kinematic Viscosity, 100 °C	D 445	mm ² /s	7.4
Viscosity Index	D 2270	-	178
Brookfield Viscosity, -40 °C	D 2983	Pa.s	32
Pour Point	D 97	°C	-45
Flash Point, P-M	D 93	°C	170

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Product Data Sheet includes a selection of specifications, for full overview please consult the Q8Oils website.