

Q8 Coolpro Long Life Premixed

Long life coolant for Passenger Cars and Commercial Vehicles

Description

Q8 Coolpro Long Life Premixed is an outstanding coolant that protects against freezing, boiling and corrosion of the cooling system. Premixed with water, the antifreeze forms a cooling liquid that transfers the heat from the combustion engine to the radiator. The long life of the Q8 Coolpro Long Life Premixed is obtained by non-depleting corrosion inhibitors.

Applications

Q8 Coolpro Long Life Premixed is used in cooling systems of all automotive passenger cars, commercial vehicles, busses and stationary internal combustion engines. It is also suited for most types industrial heat transfer and cooling systems.

Benefits

- Exceptional long life protection against all forms of corrosion.
- Reduces repairs of thermostat, radiator and water pump thus cost and downtime
- Superior and extended corrosion protection due to synergistic effects.
- Best-in-class cavitation corrosion prevention.
- Environmentally friendly corrosion inhibitor package.

Specifications & Approvals

| | | | |
|-------------------------|--------------------|-------------------------------------|--------------------|
| CUNA | NC 956-16 | Seat | |
| Case New Holland | MAT 3624 | Thermo King | |
| FVV Heft | R 443 | UNE | 26-361-88/1 |
| JASO | M325 | VAG | VW TL 774 D (G12) |
| MIL-Belgium | BT-PS-606 A | VAG | VW TL 774 F (G12+) |
| MIL-France | DCSEA 615/C | Volvo Construction Equipment | |
| MIL-Italy | E/L-1415b | Volvo Penta | |
| MIL-Sweden | FSD 8704 | Volvo Trucks | |
| MTU | MTL 5048 | Waukesha | |
| NATO | S-759 | Wärtsilä | 32-9011 |
| Opel Vauxhall | GMW 3420 | Yanmar | |
| Porsche | | Önorm | V5123 |
| Renault | 41-01-001/S Type D | Škoda | |
| SAE | J 1034 | Škoda | |
| Seat | | | |

Properties

| | Method | Unit | Typical |
|---------------------------|--------|------|---------------|
| Density, 15 °C | D 4052 | g/ml | 1.184 |
| Colour | Visual | - | Orange to Red |
| Freezing Protection | D 1177 | °C | -38 |
| Equilibrium boiling point | D 1120 | °C | 107 |
| pH | D 1287 | - | 8.2 |
| Water content | D 1123 | % | 51.4 |

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

Replacement of the coolant is recommended after 4 years.