

Q8 Garden Oil SAE 30

4 Stroke engine oil for garden equipment

Description

Q8 Garden Oil SAE 30 is a high quality monograde mineral oil designed to fulfill the requirements of some small engines used in garden equipment applications. Due to carefully selected components it is able to supply the right protection against wear, rust, oxidation and maintain an excellent level of cleanliness also in the most severe conditions. Q8 Garden Oil SAE 30 offers an extremely high thermal and mechanical stability and long lasting performances. A strong deposits control allows a very good cleanliness.

Applications

Small 4-stroke gasoline or diesel engines in lawn mowers, concrete mixers, small motor-driven electric generators, etc.

Benefits

- Prevents wear due to very good film strength.
- Excellent protection against rust and corrosion.
- Excellent protection against piston ring-sticking and varnish deposits.

Specifications, recommendations and approvals

API CC API SF

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,891
Viscosity Grade	-	-	SAE 30
Kinematic Viscosity, 40 °C	D 445	mm ² /s	99.6
Kinematic Viscosity, 100 °C	D 445	mm ² /s	11.3
Viscosity Index	D 2270	-	99
Total Base Number	D 2896	mg KOH/g	7.5
Pour Point	D 97	°C	-27
Flash Point, P-M	D 93	°C	202
Sulfated Ash	D 874	% mass	1.3
Borderline Pumping Temperature	D 3829	°C	-23

The figures above are not a specification. They are typical figures obtained within production tolerances.