

Q8 Outboard 2T

Leisure boat fluid

Description

Q8 Outboard 2T is an advanced low-smoke leisure boat fluid. This pre-diluted lubricant offers optimum performance in 2-stroke outboard engines, both with pre-mix systems and in oil injection lubrication systems. Q8 Outboard 2T is based on a special ashless additive technology to provide high wear protection. Its anti-rust properties lead to a longer service life of the engine.

Applications

Q8 Outboard 2T is highly recommended in water-cooled engines and exceeds the maximum international specifications NMMA TC-W3. It has been tested in the OMC 70HP and DFI Mercury 225HP engines.

Benefits

- Excellent cylinder protection against scuffing wear.
- Excellent protection against piston ring-sticking and varnish deposits.
- Outstanding protection against spark plug fouling and pre-ignition.
- Excellent exhaust system blockage reduction.
- Excellent protection against rust and corrosion.

Specifications & Approvals

NMMA TC-W3

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,870
Kinematic Viscosity, 40 °C	D 445	mm ² /s	40
Pour Point	D 97	°C	-35
Flash Point, COC	D 92	°C	85
Sulfated Ash	D 874	% mass	-

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

It is advisable to adopt a concentration that complies with the requirements of the engine manufacturer.