

Q8 Racing 2T

Fully synthetic motorcycle fluid

Description

Q8 Racing 2T is an exceptional fully synthetic motorcycle fluid that guarantees extreme performance in air- and water-cooled engines. Its superior formulation, based on low ash technology, results in exceptional cleanliness and detergent properties to block deposit formation. Q8 Racing 2T ensures extreme wear and seizing protection of the piston and prevents power losses.

Applications

Q8 Racing 2T is designed for competition and sports motorcycles, on- and off-road, both with lubrication premix system or oil injection system. It exceeds the requirements of ISO, API, JASO, TISI and fulfills specifications of Rotax 253 (Snowmobile) and Husqvarna 346 & Husqvarna 372.

Benefits

- Outstanding protection against piston ring sticking and exhaust system blockage.
- Excellent engine performance at extreme driving conditions.
- Outstanding protection against spark plug fouling and pre-ignition.
- Excellent protection against rust and corrosion.
- Excellent low temperature fluidity.

Specifications & Approvals

API	TC +++	JASO	FD
Global	GD	TISI	
ISO	L-EGD		

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,871
Kinematic Viscosity, 40 °C	D 445	mm ² /s	54.7
Pour Point	D 97	°C	-45
Flash Point, COC	D 92	°C	111
Sulfated Ash	D 874	% mass	0.1

The figures above are not a specification. They are typical figures obtained within production tolerances.

Remarks

It is advisable to adopt a concentration between 1 and 2% and in any case to observe the requirements of the engine manufacturer.