

Q8 TO-4 Fluid 50

Transmission fluid for Caterpillar.

Description

Q8 TO-4 Fluid 50 is an outstanding transmission fluid, especially formulated for Caterpillar. This product offers excellent protection at low temperature conditions and facilitates easy starting. It contains additives to prevent oxidation and deposit formation. The oil is suitable for use in equipment where TO-4 fluids are prescribed.

Applications

Q8 TO-4 Fluid 50 is especially formulated for Caterpillar, but also suitable in power shift transmissions, final drives, hydrostatic transmissions, torque converters and hydraulics in heavy duty vehicles. The fluid can be used in off-highway, construction and agricultural equipment.

Benefits

- Superior gear protection under shock load conditions.
- Exceptional wear protection under heavy duty operating conditions.
- Superior protection against wear and extends component life.
- Exceptional wear protection under heavy duty operating conditions.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

Allison	C-4	Komatsu Dresser	Micro-Clutch
Caterpillar	TO-4	ZF	TE-ML 03C
Eaton/Fuller			

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,899
Viscosity Grade	-	-	SAE 50
Kinematic Viscosity, 40 °C	D 445	mm ² /s	217.1
Kinematic Viscosity, 100 °C	D 445	mm ² /s	19.0
Viscosity Index	D 2270	-	98
Pour Point	D 97	°C	-18
Flash Point, COC	D 92	°C	254

The figures above are not a specification. They are typical figures obtained within production tolerances.