

Q8 Unishift PC Synt 75W-90

Synthetic API GL-4 manual transmission fluid

Description

Q8 Unishift PC Synt 75W-90 is a superior manual transmission fluid for passenger cars and light duty vehicles. This versatile lubricant offers exceptional protection and durability, even under extreme pressure, and provides best-in-class thermal stability, making it suitable for a wide variety of passenger car applications. It meets the requirements of most OEMs based on API GL-4.

Applications

Q8 Unishift PC Synt 75W-90 is a versatile lubricant designed to be used in passenger cars and light duty synchromesh manual gearboxes and transaxles, specifically in high load carrying situations. It meets the API GL-4 specification and the requirements of most European and Asian manufacturers.

Benefits

- Exceptional low temperature fluidity and wide temperature operating range.
- Exceptional internal friction reduction.
- Excellent easy gear shifting at low temperatures.
- Superior protection against wear and extends component life.
- Superior protection against rust and corrosion.

Specifications, recommendations and approvals

API	GL-4	Honda	MTF II/SG
Alfa Romeo		Honda	Special MTF
BMW/MINI		MB	235.10
Fiat	9.55550-MX3	Mitsubishi	
Fiat	9.55550-MZ1	Nissan	
Ford	M2C 175-A	PSA	B71 2330
Ford	M2C 186-A	Toyota	
Ford	M2C 200-B	VAG	VW G 052 145
Ford	M2C 200-C	Volvo	97308
GM	1940768	Volvo	97309
Honda	MTF 94	Volvo	97310

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	0,868
Viscosity Grade	-	-	SAE 75W-90
Kinematic Viscosity, 40 °C	D 445	mm ² /s	87
Kinematic Viscosity, 100 °C	D 445	mm ² /s	15.6
Viscosity Index	D 2270	-	191
Brookfield Viscosity, -40 °C	D 2983	Pa.s	25
Pour Point	D 97	°C	-45
Flash Point, P-M	D 93	°C	196

The figures above are not a specification. They are typical figures obtained within production tolerances.