

Q8 Coolblu Premixed 50

Coolant for Passenger Cars and Commercial Vehicles

Description

Q8 Coolblu Premixed 50 is an outstanding coolant that protects against freezing, boiling and corrosion of the cooling system. Premixed with water, the antifreeze forms a cooling liquid that transfers the heat from the combustion engine to the radiator. The effective protection of Q8 Coolblu Premixed 50 is obtained by inorganic acid corrosion inhibitors.

Applications

Q8 Coolblu Premixed 50 is used in cooling systems of all automotive passenger cars, commercial vehicles, busses and stationary internal combustion engines. It is also suited for most types industrial heat transfer and cooling systems.

Benefits

- Advanced protection against all forms of rust and corrosion.
- Reduces repairs of thermostat, radiator and water pump thus cost and downtime
- Effective corrosion protection due to synergistic effects of inhibitors.
- Optimal cavitation corrosion prevention.
- Environmentally friendly corrosion inhibitor package.

Specifications, recommendations and approvals

Afnor	NF R 15-601	SAE	J 1034
BS	6580	UNE	26-361-88/1
CUNA	NC 956-16	Önorm	V5123

Properties

	Method	Unit	Typical
Density, 15 °C	D 4052	g/ml	1.184
Colour	Visual	-	Blue
Appearance (Emulsion)	Visual	-	Bright & Clear
Freezing Protection	D 1177	°C	-34
Boiling Point	-	°C	105
pH	D 1287	-	9.3
Water content	D 1123	%	51.6

The figures above are not a specification. They are typical figures obtained within production tolerances.